## **ALTADENA** COMMUNITY STANDARDS DISTRICT (CSD) 320 W. Temple St., Los Angeles, CA 90012 | (213) 974-6411 | General Inquiries: info@planning.lacounty.gov | Website: http://planning.lacounty.gov

COMMUNITY WIDE DEVELOPMENT	FENCES, WALLS & LANDSCAPING (22.306.070.A.3)
STANDARDS	Corner or Reversed Corner Lots: 3 ½ ft high within 10 ft of ROW
Landscaping maintenance (22.306.060.A)	line; 6 ft high when >10 feet back from the ROW line towards
Hillside Management (22.306.060.B)	the property
Significant Ridgeline Protection (22.306.060.C) – see criteria	All Other Lots: 3 ½ ft high within Driveway zone; 6 ft high
Historic Preservation (22.306.060.D)	outside Driveway zone
Other: Equestrian District	☐ Driveway Zone area – refer to 22.306.020
☐ West Altadena 22.70	
Trest Intuction 22.70	GROSS STRUCTURAL AREA (GSA)/LOT COVERAGE
D 1 70NE	(22.306.070.A.4)
R-1 ZONE	$\square$ "GSA" includes the total floor area of <u>all enclosed</u> areas of a
YARD SETBACK REQUIREMENTS	residence, including storage, but excluding cellars and garages or
FRONT YARD (22.306.070.A.1)	<u>carports</u> .
20' for all disaster recovery rebuilds.	$\square$ "Lot coverage" includes <u>all structures</u> erected on the property.
☐ NOTE: Setback District supersedes the CSD	Neither the maximum GSA nor the maximum lot coverage shall
	exceed the following:
SIDE YARD	$(.25 \times net \ area \ of \ a \ lot) + 1,000 \ square \ feet$
$\square$ 10% of the average width of the lot or parcel, but in no case less	☐ In no event shall the maximum GSA or lot coverage exceed
than (22.306.070A.1)	9,000 sq. ft.
5' for interior and corner side yards; and	
$\square$ 10' for reverse corner side yards (whichever is greater).	PARKING REQUIREMENTS (22.306.070.A.5)
_ , , , , , , , , , , , , , , , , , , ,	1-4 bedrooms = 2 covered parking spaces (garage/carport)
REAR YARD (depends on lot size) (see 22.306.070.A.1)	5-6 bedrooms = 3 parking spaces*
Rear Yard Setbacks:	$\Box$ 7 or more = 4 (+1 space for every 2 additional bedrooms)*
Less than 20,000 sq. ft. 25'	*Where 3 or more parking spaces are required, such spaces in excess of
Equal or greater than 20,000 sq. ft. 35'	the 2 required covered parking spaces, may be uncovered and
Where a lot is less than 75 feet in depth, such lot may have a rear yard	developed in tandem.
equal to 20 percent of the average depth, but in no event less than	developed in idiaem.
10 feet in depth. (22.110.080.D)	GARAGE/CARPORT REQUIREMENTS
10 Jeel in depin. (22.110.000.D)	Minimum size: 8 ½' wide x 18' length per parking space (measure
ELACIOT SETDACUS	
FLAG LOT SETBACKS	between interior walls/posts).
Uniform 10' setback is permissible	Provides 10' driveway access and 26' backup space
GENERAL DEDICATIONS	Tandem is for 2-vehicles ONLY (8 ½' x 36').
STREET DEDICATIONS	Garage setbacks along interior side and rear can be 0' only if the
☐ In addition to the required yard setback requirements, street	following conditions are met:
dedications must be maintained unless waived by Public Works	1. Detached Garage is more than 75' from front lot line
Land Development Division. If the dedication is waived, a letter	2. Detached Garage does not cover more than 50% rear yard
from DPW will be required at the time the application is submitted.	3. 1-story not to exceed 15' in height
	4. Roof drainage to be maintained on site
<u>HEIGHT REQUIREMENTS</u>	
☐ No portion of any structure shall exceed 23' in height where located	<u>DRIVEWAY REQUIREMENTS</u>
within 15' of any property line. (22.306.070.A.1.c)	Driveway access width shall be:
Height is dependent on net lot size (22.306.070.A.2):	10' – 1 or 2 units
≥ 20,000 35'	18' – 3 to 9 units
<20,000 30'	20' – 10 or more units
Flag Lots 30'	☐ Maintain 26' back-up space in front of each required parking.
Elevation plans must show fill material and grade cuts, natural	
grade and finished grade. Include cross sections where needed.	NONCONFORMING (22.306.070.A.6)
2 stories max. above grade (basement is included as one story).	☐ Applicable only in R-1 zones. Any building or structure
2 stories man. doore grade (ousement is mended as one story).	nonconforming due to use and/or standards which is
Basement = A is more than $B$	damaged/destroyed may be restored to the conditions in which it
*Cellar not considered a story	was immediately prior to the occurrence of such
A A	damage/destruction does not exceed 100% of the total market
T   A	value of the building/structure as determined by the methods set
	forth in section (22.172.020.G.1.a&b)
	join in seemon (22.1/2.020.0.1.ucco)
natural grade B natural grade	DISTANCE BETWEEN BUILDINGS
▼	6' between accessory buildings
	10' between primary buildings
	20' between guest house and primary residence
	35' between equine buildings and habitable structures

HOME-BASED OCCUPATIONS (22.306.070.7)	HEIGHT & SETBACK REQUIREMENTS (22.306.070.C.5)
Maximum 2 businesses per property (must be within SFR)	Structures over 25' in height adjacent to R-1 or R-2 zones shall be
1 client/1 client vehicle total per hour per property	setback an additional foot from the inside of said interior side for
2 employees/volunteers maximum per property	every 2' in height and an additional foot from the inside of said
Additional businesses allowed:	rear yard for every 1' in height
☐ Digital photo lab ☐ Picture Framing ☐ Seamstress/tailor	NOT IN COUNTY JURISDICTION
DED & DDEAVEACT (22 206 070 4 9)	
BED & BREAKFAST (22.306.070.A.8)	If property abuts other property not in county jurisdiction, see
Requires Conditional Use Permit.	(22.306.070.C.6)
D 170NE	COMMEDCIAL ZONEC
R-2 ZONE	COMMERCIAL ZONES (22.306.070.D)
HEIGHT REQUIREMENTS (22.306.070,B.1)	Drive-through facilities: CUP and additional standards.
$\square$ Equal to or less than 20,000 sq. ft. = 30'	Permitted Uses (22.306.070 D.1)
$\square$ More than 20,000 sq. ft. = 35,	Uses subject to Permit (2 <b>2/</b> 306.070.D.2)
	$\square$ Development Standards (22.306.070.D.3)
<u>LANDSCAPING</u> (22.306.070 B.1.2)	Parking / Design Standards
50% landscaping required within front yard setback.	Height Buffers
	☐ FAR / ☐ Pedestrian Character
YARD SETBACK REQUIREMENTS	☐ Signage
☐ Same as R-2 in Title 22	
Front yard: 20'	C-2 ZONE
Rear yard: 15'	$\square$ Permitted Uses (22.306.070.E.1)
Interior/Corner side: 🖎	Uses sybject to Permit (22.306.070.E.2)
Reverse corner side: 10'	
Street/Highway dedication(s) - In addition to the above	<u>C-3/ZONE</u>
required yard setbacks, the dedication must also be maintained	Uses subject to Permit (22.306.070.F)
unless a dedication waiver is obtained from DPW – Land	
Development Division.	C M ZONE
	<u>C-M ZONE</u>
BUILDING DESIGN REQUIREMENTS (22.30 (070.B.3)	Uses subject to Permit (22.306.070.G.1)
Rooflines on any side of a structure exceeding 30 Seet in length shall	☐ Floor Area Ratio: total gross floor area of a lot shall not exceed 1.0
be broken into smaller sections by use of decorative elements such	times the total area of such lot. (22.306.070.G.2)
as dormers, gables, eyebrows, parapets, mansards, oxother design	
features.	M-1 ZONE
$\square$ Floor area shall be at least 20% less than the floor area of the $1^{st}$	Floor Area Ratio: total gross floor area of a lot shall not exceed 1.0
story and shall be set back <u>ONLY</u> from the side and/or rear of the	times the total area of such lot. (22.306.070.H)
1 <sup>st</sup> floor structure.	
Attached garages and other attached non-living areas shall be	AREA-SPECIFIC DEVELOPMENT
included in computing the floor area of the first story.	
	<u>STANDARDS</u>
BED & BREAKFAST (22.306.070.B.4)	Lake Avenue Mixed-Use "Center" Area (22.306.080.A)
Requires Conditional Use Permit	Height & FAR
R-3 ZONE	MODIFICATION OF DEVELOPMENT
YARD REQUIREMENTS	STANDARDS
Interior Side Yards (22.306.070.C.2)	SIGNIFICANT RIDGELINES
The following only applies where R-3 property adjoins R-1 and R-2	Process and Additional Findings (22.306.090.A)
zones	1 Tocess and Additional Findings (22.300.090.A)
$\square$ Interior side yards adjoining R-1 or R-2 zones shall be	RESIDENTIAL ZONES
landscaped with shrubs and/or trees for shielding.	☐ Applicability (22.306.090.B)
no driveway, walkway, patio slab, or other hard surface	Application Materials and Fees (22.306.090.B.2)
material is allowed within interior side yard.	Additional Development Standards (22.306.090.B.3)
no uncovered porch, platform, landing, deck or balcony	Procedure, Findings and Conditions (22.306.090.B.4)
may project into interior side yard	1 Tocedure, 1 maings and conditions (22.500.090.B.4)
	COMMERCIAL ZONES
Rear Yards (22.3)6.070.C.3)	Applicability (22.306.090.C.1)
Shall include a landscaped area with a minimum depth of	Application Materials and Fees (22306.090.C.2)
10' measured from the rear lot line	Additional Development Standards (2, 306.090.C.3)
$\square$ 1/tree (15-gallon min. size) per every 250 sq. ft. of	Procedure, Findings and Conditions (22,306.090.C.4)
laydscaped area	1 roceaure, Pinaings and Conditions (22.300.070.C.4)
	LAKE AVENUE MIXED USE 'CENTER' AREA
BUILDING DESIGN REQUIREMENTS (22.306.070.C.4)	Applicability (22.306.090.D.1)
Rooflines exceeding 30' in length shall be broken into smaller	Application Materials fees (22.306.090.D.2)
sections with decorative elements such as dormers, gables,	Procedure, Findings and Conditions (22.306.090.D.4)
eyebrows, parapets, mansards or other features.	